

## *Affordable and Easy-to-use*

- TI TITAN chipset and TI voice engine
- 2 programmable keys, Auto provision
- 1xLAN, 1xdual-color LED, Phone label
- Power over Ethernet, Wall-mountable



The SIP-T18P is the simply IP phone that equipped with TI TITAN chipset, comprehensive telephony features, PoE, auto provision, and interoperable with the leading IP-PBX and soft switch. It is economical and can be desktop or wall mounted.

Designed for working environment needing a basic feature IP phone, the SIP-T18P is a very cost-effective choice for small business, SOHO and Hotel, college apartment, supermarket, and warehouse etc.

## Phone Features

1 VoIP account, Hotline  
Call waiting, Call transfer, Call forward  
Call hold, Mute, Redial, DND  
3-way conferencing, Speed dial  
Direct IP call without SIP proxy  
Volume control, Ringtone selection  
Tone scheme, System log export  
Integrated Voice Response System

## IP PBX System Integration

Music on hold  
Call park, Call pickup  
Dial plan, Dial now  
Voicemail  
Message Waiting Indication (MWI)  
Distinctive ringtone

## Voice Features

Wideband codec: G.722  
Narrowband codec: G.711 $\mu$ /A, G.726,  
G.729AB, G.723.1  
VAD, CNG, PLC, AJB, AGC

## Network Features

SIP v1 (RFC2543), v2 (RFC3261)  
NAT Traversal: STUN mode  
DTMF: In-band, out-of band (RFC2833) and SIP INFO  
Proxy mode and peer-to-peer SIP link mode  
IP Assignment: Static/DHCP  
TFTP/DHCP client  
Telnet/HTTP server  
DNS client

## Management

Built-in HTTP web server  
Configuration: browser/phone/auto-provision/IVR  
Auto provision via TFTP/FTP/HTTP/PnP  
Auto provision for firmware, configuration, ringtone etc

## Security

QoS: IEEE 802.1p/q tagging (VLAN), Layer 3ToS  
Digest authentication using MD5/MD5-sess  
Secure configuration file via AES encryption  
Admin/user configuration mode

## Physical Features

TI TITAN chipset  
20 keys including 2 programmable keys  
4 feature keys (Transfer/Hold/Mute/Redial)  
Phone label  
1xdual-color LED  
1xRJ45 10/100M Ethernet port  
Desktop with footstand (detachable),  
Wall-mountable  
Power adapter: AC 100~240V input  
and DC 5V/1.2A Output  
Power over Ethernet  
(IEEE 802.3af class 1) optional  
Operating humidity: 10~95%  
Storage temperature: up to 60°C

## Package Features

Qty/CTN: 10 PCS  
N.W/CTN: xx KG  
G.W/CTN: xx KG  
Measurement: 0.054CMB  
Carton Meas: 520x470x220MM

## Certifications

