



December 7, 2017

Greetings,

BroadSoft is pleased to announce that the Yealink T2XX series has been formally validated with BroadWorks. The device model(s) listed below have been validated as interoperable with the BroadWorks SIP interface. Configuration details and any issues or limitations identified during the interoperability testing are documented in the BroadSoft Partner Configuration Guide (PCG) *PartnerConfigGuide Yealink T2XX Series*. The PCG is available to BroadSoft customers on the BroadSoft Xchange website at xchange.broadsoft.com.

BroadSoft validates that the device interoperates with the BroadWorks SIP interface. BroadSoft does not validate qualitative aspects of the device, capacity, or other device capabilities outside the scope of the SIP signaling interface.

The validation covers the Yealink version(s) and BroadWorks release listed below. Other versions tested previously are documented in the PCG.

Yealink Models and Versions*:

T29G:	46.82.0.20
T27P:	45.82.0.20
T27G:	69.82.0.20
T23P:	44.82.0.20
T23G:	44.82.0.20
T21 E2:	52.82.0.20
T21P E2:	52.82.0.20
T19 E2:	53.82.0.20
T19P E2:	53.82.0.20

BroadWorks Release 22.0

*This validation also applies to all subsequent compatible maintenance releases to this device version.

Best Regards,

A handwritten signature in black ink that reads 'Wesley Hacker'.

Wesley Hacker
Director, Solutions Engineering
+1.240.364.5149
wesley@broadsoft.com