

April 16, 2019

Greetings,

Cisco is pleased to announce that the Yealink T2xx series has been formally validated with BroadWorks. The device model(s) listed below have been validated as interoperable with the BroadWorks SIP interface. Configuration details and any issues or limitations identified during the interoperability testing are documented in the BroadWorks Partner Configuration Guide (PCG) *PartnerConfigGuide Yealink T2XX Series*. The PCG is available to Cisco BroadWorks customers on the BroadSoft Xchange website at [xchange.broadsoft.com](http://xchange.broadsoft.com).

Cisco validates that the device interoperates with the BroadWorks SIP interface. Cisco does not validate qualitative aspects of the device, capacity, or other device capabilities outside the scope of the SIP signaling interface.

The validation covers the Yealink version(s) and BroadWorks release listed below. Any versions tested previously are documented in the PCG.

Yealink T27G version 69.84.0.10\*  
Yealink T23P version 44.84.0.10\*  
Yealink T23G version 44.84.0.10\*  
Yealink T21P E2 version 52.84.0.10\*  
Yealink T19P E2 version 53.84.0.10\*  
BroadWorks Release 22.0

\*This validation also applies to all subsequent compatible maintenance releases to this device version.

Best Regards,



**Feng Wei**  
Sr. Engineer  
+1.240.364.5129  
[fewei@cisco.com](mailto:fewei@cisco.com)