| Yealink T3 Series IP Phones Specification |   |   |   |
|---|---|---|---|
| Model                                     | T30/T30P                                      | T31/T31P/T31G                                 | T33P/T33G                                     |
|   |   |   |   |
| LCD                                       | 2.3" Graphical LCD                            | 2.3" Graphical LCD                            | 2.4" Color LCD                                |
| Resolution                                | 132 x 64                                      | 132 x 64                                      | 320 x 240                                     |
| LCD Backlight                             | X   | √ (Adjustable Brightness)                     | √ (Adjustable Brightness)                     |
| Line                                      | 1   | 2   | 4   |
| Line Key                                  | 0   | 2   | 4   |
| Memory Key                                | 0   | 2   | 12 (4 Pages of 3 Keys)                        |
| PoE                                       | √ (T30P)                                      | √ (T31P/T31G)                                 | √   |
| GigE                                      | X   | √ (T31G)                                      | √ (T33G)                                      |
| Wireless Headset Adapter                  | EHS35   | EHS35   | EHS35   |
| N-Way Audio Conferencing                  | 5   | 5   | 5   |
| Wide-band Codecs                          | G.722   | G.722   | G.722   |
| Narrow-band Codecs                        | G.711 (A/μ), G.729AB, G.726,<br>iLBC, G.723.1 | G.711 (A/μ), G.729AB, G.726,<br>iLBC, G.723.1 | G.711 (A/μ), G.729AB, G.726,<br>iLBC, G.723.1 |
| Foot Stand                                | 2 Adjustable Angles                           | 2 Adjustable Angles                           | 2 Adjustable Angles                           |
| Wall Mounting                             | √   | $\sqrt{}$                                     | √   |
| Security Slot                             | √   | √   | √   |
| External Yealink<br>AC Adapter (optional) | AC 100~240V Input and DC 5V/600mA Output      | AC 100~240V Input and DC 5V/600mA Output      | AC 100~240V Input and DC 5V/600mA Output      |

Issued by Yealink (Xiamen) Network Technology CO., Ltd. All rights reserved. Subject to changes in technology, design and availability.





# Yealink T3 Series IP Phones

Facilitate the communication, enrich your business



Yealink new T3 series is a classic and cost-effective entry-level business IP phone for daily desktop voice communications. Featuring superior HD audio performance, 5-way local conference function, EHS wireless headset supporting, and proven integration of Yealink Device Management Platform, T3 series maximizes productivity and enhances collaboration for businesses of various scales.

### **Stronger Performance, More Possibilities**

Equipped with powerful chip, the T3 series owns a stronger computing ability and more upgraded functions, which ensures a higher productivity and smoother office experience. Due to great performance, T3 series is capable to extend more services for different business demands.



## **Superior HD Audio, Better Communication**

The Yealink T3 series provides distraction-free communications with industry leading Smart Noise Filtering Technology, which delivers excellent sound quality without extraneous noises and allows fluent conversations.



Smart Noise Filtering

# **Classic Design, Practical Details**

Designed by Yealink original team, T3 series inherits the design concept of Yealink IP phone family. The advanced design including modern appearances and ergonomic details enables easier and friendly operation experience to users.



### All in One Platform, Convenient Management

Proven reliability and integrations for Yealink Device Management Platform, installed the unified firmware, T3 series is simple to deploy and manage, which allows a significant reduction in the operation and maintenance cost.

